



Hand held remote includes many features like, I-Feel, X-Fan, and Sleep Mode.

- ▶ Connect up to FIVE indoor units
- ▶ Outdoor sound range (56-59 db)
- ▶ Port adapters included
- ▶ 9000, 12000, 18000, & 24000 BTUH high wall mounted indoor models available
- ▶ Hand held remote controller included with each indoor unit
- ▶ Inverter driven (Variable Speed Compressor)
- ▶ Blue Fin Coastal coating
- ▶ AHRI Certified System

15 Series Multi-Zone Outdoor Heat Pump

Outdoor	SEER	HSPF	EER	Capacity (BTUH) Cooling	Capacity (BTUH) Heating	Voltage	Number of Ports	Gas Line	Liquid Line	Max Overcurrent Protection
M4THM1518A12NB	15	8.2	10.0	18000	19000	208-230/60/1	2	3/8" (2)	1/4" (2)	20
M4THM1524A13NB	15	8.2	8.0	26000	29000	208-230/60/1	3	3/8" (3)	1/4" (3)	30
M4THM1530A14NB	15	8.2	8.0	29000	30400	208-230/60/1	4	3/8" (4)	1/4" (4)	45
M4THM1536A14NB	15	8.2	7.8	34000	35800	208-230/60/1	4	3/8" (2) 1/2" (1) 5/8"(1)	1/4" (3) 3/8" (1)	45
M4THM1542A15NB	15	8.2	9.1	40000	44500	208-230/60/1	5	3/8" (2) 1/2" (2) 5/8"(1)	1/4" (4) 3/8" (1)	50

5 YEAR WARRANTY

Limited functional parts warranty¹

10 YEAR WARRANTY

Functional parts warranty with product registration¹

¹ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on americanstandardair.com. Ask your dealer for full warranty information at time of purchase. Warranties are for residential and multi-family use only, some exclusions may apply. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

High Wall Mounted Indoor Unit

15 SEER	Nominal Capacity (BTUH)	Voltage	Gas Line	Liquid Line
M4MHW1709A1NOA	9000	208-230/60/1	3/8"	1/4"
M4MHW1712A1NOA	12000	208-230/60/1	3/8"	1/4"
M4MHW1718A1NOA	18000	208-230/60/1	1/2"	1/4"
M4MHW1724A1NOA	24000	208-230/60/1	5/8"	1/4"

Ductless Multi-Zone Approved Combinations

Outdoor Unit	Indoor Unit Combinations with Associated Nominal Capacity (kBTUH)									
	Two Units		Three Units			Four Units			Five Units	
M4THM1518A12NB 18,000 BTUH	9+9		12+12							
	9+12									
M4THM1524A13NB 24,000 BTUH	9+9		9+12		9+9+9			9+12+12		
	9+18		12+12		9+9+12		9+9+18			
	12+18		18+18							
M4THM1530A14NB 30,000 BTUH	9+9		9+12		9+9+9		9+9+12		9+9+18	
	9+18		12+12		9+12+12		9+1+18		12+12+12	
	12+18		18+18		12+12+18					
M4THM1536A14NB 36,000 BTUH	9+9		12+18		9+9+9		9+12+18		12+12+18	
	9+12		12+24		9+9+12		9+12+24		12+12+24	
	9+18		18+18		9+9+18		9+18+18		12+18+18	
	9+24		18+24		9+9+24		9+18+24		18+18+18	
	12+12		24+24		9+12+12		12+12+12			
M4THM1542A15NB 42,000 BTUH	9+9		12+18		9+9+9		9+12+24		12+12+24	
	9+12		12+24		9+9+12		9+18+18		12+18+18	
	9+18		18+18		9+9+18		9+18+24		12+18+24	
	9+24		18+24		9+9+24		9+24+24		12+24+24	
	12+12		24+24		9+12+12		12+12+12		18+18+18	
					9+12+18		12+12+18		18+18+24	