



- ▶ Mix and match up to 5 indoor units to achieve 42K BTUH heating and cooling
- ▶ Low ambient heating down to -22° F
- ▶ Energy Star® certified—eligible for rebates
- ▶ Outdoor unit sound levels as low as 56 dB(A)
- ▶ Port adapters included
- ▶ 9000, 12000, 18000, & 24000 BTUH high wall mounted indoor models available
- ▶ Handheld remote controller included with each indoor unit
- ▶ Blue Fin Coastal coating

Outdoor	SEER2	HSPF2	EER2	Capacity (BTUH) Cooling	Capacity (BTUH) Heating	Voltage	Gas Line	Liquid Line	Max Overcurrent Protection	Low Ambient Heating Capability
M4THM1918A12NA	19	10	12	17000	18000	208/230	3/8"	1/4"	20	-22° - 75°F -30° - 24°C
M4THM1924A13NA	19	10	12.5	23200	24000	208/230	3/8"	1/4"	25	-22° - 75°F -30° - 24°C
M4THM1930A14NA	19	10	12.5	28400	30000	208/230	3/8"	1/4"	35	-22° - 75°F -30° - 24°C
M4THM1936A14NA	19	10	12	34000	36000	208/230	3/8"	1/4"	45	-22° - 75°F -30° - 24°C
M4THM1942A15NA	19	10	12	36000	40000	208/230	3/8"	1/4"	45	-22° - 75°F -30° - 24°C

5 YEAR WARRANTY

Limited functional parts warranty¹

10 YEAR WARRANTY

Functional parts warranty with product registration¹

¹ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on americanstandardair.com. Ask your dealer for full warranty information at time of purchase. Warranties are for residential and multi-family use only, some exclusions may apply. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

Compatible 15 SEER and 23 SEER2 High Wall Mounted Indoor Units

15 SEER	Nominal Capacity (BTUH)	Voltage	Gas Line	Liquid Line
M4MHW1709A1NOA	9000	208-230/60/1	3/8"	1/4"
M4MHW1712A1NOA	12000	208-230/60/1	3/8"	1/4"
M4MHW1718A1NOA	18000	208-230/60/1	1/2"	1/4"
M4MHW1724A1NOA	24000	208-230/60/1	5/8"	1/4"
23 SEER2	Nominal Capacity (BTUH)	Voltage	Gas Line	Liquid Line
M4MHW2309A1NOA	9100	208-230/60/1	3/8"	1/4"
M4MHW2312A1NOA	12000	208-230/60/1	1/2"	1/4"
M4MHW2318A1NOA	18200	208-230/60/1	5/8"	1/4"
M4MHW2324A1NOA	22000	208-230/60/1	5/8"	1/4"



Ductless Multi-Zone Approved Combinations

Outdoor Unit	Indoor Unit Combinations with Associated Nominal Capacity (kBTUH)									
	Two Units		Three Units			Four Units			Five Units	
M4THM1918A12NA 18,000 BTUH	9+9		12+12							
	9+12									
M4THM1924A13NA 24,000 BTUH	9+9		9+12		9+9+9		9+12+12		12+12+12	
	9+18		12+12		9+9+12		9+9+18			
	12+18		18+18							
M4THM1930A14NA 30,000 BTUH	9+9		9+12		9+9+9		9+9+12		9+9+18	
	9+18		12+12		9+12+12		9+1+18		12+12+12	
	12+18		18+18		12+12+18					
M4THM1936A14NA 36,000 BTUH	9+9		12+18		9+9+9		9+12+18		12+12+18	
	9+12		12+24		9+9+12		9+12+24		12+12+24	
	9+18		18+18		9+9+18		9+18+18		12+18+18	
	9+24		18+24		9+9+24		9+18+24		18+18+18	
	12+12		24+24		9+12+12		12+12+12			
M4THM1942A15NA 42,000 BTUH	9+9		12+18		9+9+9		9+12+24		12+12+24	
	9+12		12+24		9+9+12		9+18+18		12+18+18	
	9+18		18+18		9+9+18		9+18+24		12+18+24	
	9+24		18+24		9+9+24		9+24+24		12+24+24	
	12+12		24+24		9+12+12		12+12+12		18+18+18	
					9+12+18		12+12+18		18+18+24	